

HOS CALEDONIA

HOSMAX320 Offshore Supply Vessel



DIMENSIONS AND REGULATORY INFORMATION										
Length:	319 ft 6 in	(97.4 m)	Beam:	64 ft 0 in (19.5	m)	Draft Max:	19 ft 4 in (5.89 m)			
-						Draft Min:	10 ft 0 in (3.05 m)			
Gross:	3,835 GT		<u>Net:</u>	1,283 NT						
<u>IMO:</u>	9647629		<u>O.N.:</u>	1244585		Flag:	U.S.			
Certifications:		Oceans-SOLAS, USCG Subchapter I, USCG Subchapter L								
Classifications:	Loadline, A	Loadline, American Bureau of Shipping, +DPS-2, FFV-1, (E), +A1, +ACCU, +AMS, OSV, UWILD, ACP, CRC, OSR-C2								
PERFORMANCE										
Cruise Speed:	9.0 kts	170 gal/hr (643 l/hr) <u>M</u>	ax Speed:	11.0 kts	297 gal/hr (1,124 l/hr)			
On DP:		86 gal/hr (326 l/hr) On Standby: 51 gal/hr (193 l/hr)				93 l/hr)				
PROPULSION, MACHINERY AND STEERING										
Main Engines:		2 x Caterpilla	r 3516C			Tot	al Horsepower:	6,008 bhp		
Propellers:		CPP, High Eff	iciency, 4-Blade			Pro	peller Diameter:	106 in (2,692 mm)		
Primary Generators: 2 x Caterpillar			r C 32			Tot	al Rating:	1,430 kW		
Bow Thruster:	ow Thruster: 2 x Brunvoll C			.PP Tunnel			al Rating:	2,600 hp		
Stern Thruster:	Thruster: 1 x Brunvoll C			PP Tunnel			al Rating:	1,300 hp		
<u>Rudder:</u>		Fishtail, High	Lift, Independent Steering				ver Generation:	480V/60 Hz/3-Phase		
CAPACITIES AND DELIVERY RATES										
Deadweight:		6,066 LT (6,1	63 MT)			De	ck Area:	233 ft x 52 ft (12,116 ft ²)		
								71.0 m x 15.8 m (1,125.6 m²)		
<u>Deck Cargo:</u>		4,000 LT (4,0	64 MT)			De	<u>ck Load Rating:</u>	1,024 lbs/ft ² (5 MT/m ²)		
<u>Dry Bulk:</u>		12,528 ft ³ (3	55 m³)			<u>Sys</u>	stem Pressure:	80 psi (5.5 bar)		
Brine:	z0,911 bbl (3		3,224 m³)			Dis	<u>scharge Rate:</u>	1,000 GPM (227 m³/hr)		
<u>Liquid Mud:</u>	20,911 bbl (3,324 m³)			Dis	scharge Rate:	1,000 GPM (227 m ³ /hr)		
Potable Water:		59,658 gal (2	226 m³)							
<u>Rig Fuel:</u>		241,785 gal	(915 m³)			Dis	<u>scharge Rate:</u>	800 GPM (182 m³/hr)		
Rig Water:	Water: 701,587 gal		2,656 m³)			Dis	<u>scharge Rate:</u>	732 GPM (166 m³/hr)		
Cooler Area:		460 ft³ (13 m	1 ³)			Fre	ezer Area:	460 ft ³ (13 m ³)		
ELECTRONICS										

AIS, Auto Pilot, C-Nav, CCTV Cameras, Cyscan, DGPS w/ AIS, DSDL, EPIRB, GMDSS "A3", Gyro Compass, Joystick Control, Mag Compass, MAMS/VMS, Navtex, Public Phone System w/ loudhailer, Radascan, S-band Radar, SARTs, Speed Log, SSAS, VHF Radio, VHF Radio (Handheld), VSAT, Windbird, X-band Radar

ACCOMMODATIONS

13 air conditioned/heated staterooms certified for 24 person berthing.

SPECIAL FEATURES								
Oil Spill Recovery:	ABS Capability Class 2	Recovered Oil Capacity:	20,911 bbl (3,325 m ³) (>60 °C FP)					
Off-ship Firefighting:	ABS FIFI 1	Number of Fire Monitors:	2					
		Total Flow Rate:	10,586 gal/min (2,406 m³/hr)					
Deck Crane:	2 x Appleton EB70-53-33	<u>Max Lift @ Max Radius:</u>	3 MT @ 53 ft					
		<u>Max Lift @ Min Radius:</u>	13 MT @ 16 ft					
		Personnel Rating:	0.6 MT					
<u>Capstans:</u>	2 x 11 MT	_						

NOTICE: The information contained herein is provided solely for the convenience of reference, and Hornbeck does not warrant the accuracy or completeness of the data, which may vary from the current condition of the vessel or equipment. Hornbeck accepts no liability for the content of this document or for the consequences of any actions taken on the basis of the information provided, unless that information is subsequently confirmed in writing by an authorized representative.