



# HOS RED ROCK

HOSMAX300 Offshore Supply Vessel  
HOSMAX 300



## DIMENSIONS AND REGULATORY INFORMATION

<b>Length:</b>	292 ft 0 in (89.0 m)	<b>Beam:</b>	64 ft 0 in (19.5 m)	<b>Draft Max:</b>	19 ft 11 in (6.07 m)
<b>Gross:</b>	3,911 GT	<b>Net:</b>	1,173 NT	<b>Draft Min:</b>	11 ft 3 in (3.43 m)
<b>IMO:</b>	9647655	<b>O.N.:</b>	1244591	<b>Flag:</b>	U.S.
<b>Certifications:</b>	Oceans-SOLAS, USCG Subchapter I, USCG Subchapter L				
<b>Classifications:</b>	Loadline, American Bureau of Shipping, +DPS-2, FFV-1, (E), +A1, +ACCU, +AMS, OSV, ENVIRO, GP, UWILD, ACP, CRC, OSR-C2				

## PERFORMANCE

<b>Cruise Speed:</b>	10.0 kts	133 gal/hr (503 l/hr)	<b>Max Speed:</b>	12.0 kts	208 gal/hr (787 l/hr)
----------------------	----------	-----------------------	-------------------	----------	-----------------------

## PROPULSION, MACHINERY AND STEERING

<b>Main Engines:</b>	4 x Caterpillar 3516C	<b>Total Rating:</b>	7,300 kW
<b>Main Propulsion:</b>	2 x Schottel Azimuthing Z-Drives	<b>Propeller Diameter:</b>	106 in (2,692 mm)
<b>Bow Thruster:</b>	2 x Schottel FPP Tunnel	<b>Total Rating:</b>	6,700 hp
		<b>Total Rating:</b>	3,160 hp
		<b>Power Generation:</b>	690V/60/3 phase

## CAPACITIES AND DELIVERY RATES

<b>Deadweight:</b>	5,407 LT (5,494 MT)	<b>Deck Area:</b>	197 ft x 55 ft (10,835 ft <sup>2</sup> ) 60.0 m x 16.8 m (1,006.6 m <sup>2</sup> )
<b>Deck Cargo:</b>	3,350 LT (3,404 MT)	<b>Deck Load Rating:</b>	1,024 lbs/ft <sup>2</sup> (5 MT/m <sup>2</sup> )
<b>Dry Bulk:</b>	14,347 ft <sup>3</sup> (406 m <sup>3</sup> )	<b>System Pressure:</b>	80 psi (5.5 bar)
<b>Liquid Mud:</b>	20,846 bbl (3,314 m <sup>3</sup> )	<b>Discharge Rate:</b>	1,000 GPM (227 m <sup>3</sup> /hr)
<b>Methanol:</b>	1,605 bbl (255 m <sup>3</sup> )	<b>Discharge Rate:</b>	250 GPM (57 m <sup>3</sup> /hr)
<b>Potable Water:</b>	57,494 gal (218 m <sup>3</sup> )		
<b>Recovered Oil (&lt;60 deg C FP):</b>	1,605 bbl (255 m <sup>3</sup> )	<b>Discharge Rate:</b>	750 GPM (170 m <sup>3</sup> /hr)
<b>Recovered Oil (&gt;60 deg C FP):</b>	19,241 bbl (3,059 m <sup>3</sup> )	<b>Discharge Rate:</b>	750 GPM (170 m <sup>3</sup> /hr)
<b>Rig Fuel:</b>	220,168 gal (833 m <sup>3</sup> )	<b>Freezer Area:</b>	400 ft <sup>3</sup> (11 m <sup>3</sup> )
<b>Rig Water:</b>	498,523 gal (1,887 m <sup>3</sup> )	<b>Total Flow Rate:</b>	10,586 gal/min (2,406 m <sup>3</sup> /hr)
<b>Cooler Area:</b>	600 ft <sup>3</sup> (17 m <sup>3</sup> )		
<b>Off-ship Firefighting Monitors:</b>	2		

## ELECTRONICS

AIS, Anemometer, Auto Pilot, CCTV Cameras, Cyscan, Depth Sounder, DGPS w/ AIS, DSDL, EPIRB, GMDSS "A3", Gyro Compass, Joystick Control, Mag Compass, MAMS/VMS, Navtex, Public Phone System w/ loudhailer, Radascan, S-band Radar, SARTs, Speed Log, SSAS, VERIPOS, VHF Radio, VHF Radio (Handheld), VSAT, X-band Radar

## ACCOMMODATIONS

17 air conditioned/heated staterooms certified for 50 person berthing.

## SPECIAL FEATURES

<b>Deck Crane:</b>	1 x Appleton EB70-53-33	<b>Max Lift @ Max Radius:</b>	3 MT @ 53 ft
		<b>Max Lift @ Min Radius:</b>	13 MT @ 16 ft
		<b>Personnel Rating:</b>	0.6 MT
<b>Watermaker Cap.:</b>	2,000 USG/day		

NOTICE: The information contained herein is provided solely for the convenience of reference, and Hornbeck does not warrant the accuracy or completeness of the data, which may vary from the current condition of the vessel or equipment. Hornbeck accepts no liability for the content of this document or for the consequences of any actions taken on the basis of the information provided, unless that information is subsequently confirmed in writing by an authorized representative.