

HOS REMINGTON

270 Offshore Supply Vessel



	DIMENSION	IS AND REG	ULATORY INF	ORMATION	
ength: 270 ft 0 in (82.3 m	n) <u>Beam:</u>	56 ft 0 in (17.1 m)	Draft Max:	17 ft 11 in (5.46 m)	
Gross: 2,971 GT	<u>Net:</u>	1,366 NT	Draft Min:	11 ft 0 in (3.35 m)	
MO: 9686144	<u>O.N.:</u>	31015886329	<u>Flag:</u>	Mexico	
Certifications: Oceans-SOLAS					
Classifications: Loadline, ABS, +D	PS-2, FFV-1, (E), +A1, +A	MS, OSV, Supply-H	INLS, +ACC, GP, UWII	LD, OSR-C2	
		PERFO	RMANCE		
Cruise Speed: 10.0 kts 140 g	gal/hr (530 l/hr) <u>M</u>	ax Speed: 12.	5 kts 290 gal/hr (1,	,098 l/hr)	
	PROPULS	SION, MACH	IINERY AND S	TEERING	
<u> Main Engines:</u>	es: 4 x Caterpillar 3516C			Rating:	7,300 kW
Main Propulsion : 2 x Schottel Azimuthing Z-Drives			<u>Tota</u>	<u>l Rating:</u>	6,700 hp
Bow Thruster: 2 x Schottel FPP Tunnel			Tota	l Rating:	3,160 hp
			Powe	er Generation:	690V/60/3 phase
	CAP	ACITIES AN	D DELIVERY R	ATES	
<u>Deadweight:</u>	3,780 LT (3,840 MT)		Dec	k Area:	170 ft x 48 ft (8,200 ft ²)
					52.0 m x 14.8 m (761.8 m²)
<u> Deck Cargo:</u>	2,100 LT (2,134 MT)			<u>k Load Rating:</u>	1,024 lbs/ft ² (5 MT/m ²)
<u>Dry Bulk:</u>	8,492 ft ³ (240 m ³)			em Pressure:	80 psi (5.5 bar)
<u>iquid Mud:</u>	12,569 bbl (1,998 m³)		Disc	<u>:harge Rate:</u>	1,000 GPM (227 m³/hr)
Potable Water:	73,182 gal (277 m ³)				
Recovered Oil (>60 deg C FP):	overed Oil (>60 deg C FP): 12,569 bbl (1,998 m ³)				
Rig Fuel:	251,258 gal (951 m³)		Disc	<u>:harge Rate:</u>	750 GPM (170 m³/hr)
Rig Water:	384,845 gal (1,457 m³)		Disc	<u>:harge Rate:</u>	750 GPM (170 m³/hr)
Cooler Area:	570 ft ³ (16 m ³)		Free	zer Area:	435 ft ³ (12 m ³)
Off-ship Firefighting Monitors:	<u>2</u>		Tota	al Flow Rate:	10,568 gal/min (2,402 m³/hr)
		ELECT			

AIS, Anemometer, Auto Pilot, C-Nav, CCTV Cameras, Depth Sounder, DGPS w/ AIS, DSDL, EPIRB, Fanbeam, GMDSS "A3", Gyro Compass, Joystick Control, Mag Compass, MAMS/VMS, Navtex, Public Phone System w/ loudhailer, Radascan, S-band Radar, SARTs, Speed Log, SSAS, VHF Radio, VHF Radio (Handheld), VSAT, X-

band Radar

ACCOMMODATIONS

12 air conditioned/heated staterooms certified for 32 person berthing.

SPECIAL FEATURES

Stores Crane:

1 x EBI TC20-24-40

Max Lift @ Max Radius:2 MTMax Lift @ Min Radius:2 MTPersonnel Rating:1.0 MMoon Pool:36 in.

2 MT @ 40 ft 2 MT @ 10 ft 1.0 MT 36 in. dia.

NOTICE: The information contained herein is provided solely for the convenience of reference, and Hornbeck does not warrant the accuracy or completeness of the data, which may vary from the current condition of the vessel or equipment. Hornbeck accepts no liability for the content of this document or for the consequences of any actions taken on the basis of the information provided, unless that information is subsequently confirmed in writing by an authorized representative.