

## HOS TAURUS

HOSMAX280 Offshore Supply Vessel



		DIM		<b>IS AND RE</b>	<b>GULA</b> 1	ORY IN	FORMATION		
Length:	280 ft 0 in (	(85.3 m)	Beam:	60 ft 0 in (18.3	m) <u></u>	raft Max:	19 ft 3 in (5.87 m)		
					<u> </u>	raft Min:	10 ft 3 in (3.12 m)		
<u>Gross:</u>	2,998 GT		<u>Net:</u>	1,101 NT					
<u>MO:</u>	9385271		<u>O.N.:</u>	2674	<u> </u>	lag:	Vanuatu		
<u>Certifications:</u>	Oceans-SO								
<u>Classifications:</u>	Is: Loadline, American Bureau of Shipping, +DPS-2, (E), +A1, FFV 1-NS, +AMS, OSR-C2								
				PERF	ORMA	NCE			
Cruise Speed:	10.0 kts	145 gal/hr (549 l/ł	ır) <u>M</u>	ax Speed:	12.7 kts	290 gal/hr (1	1,098 l/hr)		
		PI	ROPUL	SION, MAG	CHINER	Y AND	STEERING		
Main Engines:	s: 2 x Caterpilla			r C280-8			al Horsepower:	6,598 bhp	
Propellers:	CPP, High E	CPP, High Efficiency, 4-Blade			Pro	<u>peller Diameter:</u>	106 in (2,692 mm)		
Primary Gener	ators:	2 x Caterpillar 3508B				<u>Tota</u>	al Rating:	1,820 kW	
Shaft Generators:		2 x Kato				Tota	al Rating:	4,000 kW	
Aft Bow Thruster:		1 x Rolls Royce Swing-down Azimuth				Tota	al Rating:	1,150 hp	
Fwd Bow Thruster:		1 x Brunvoll CPP Tunnel				Tota	al Rating:	1,676 hp	
Stern Thruster:		1 x Brunvoll CPP Tunnel				Tota	al Rating:	1,676 hp	
Rudder:		Independent Steering, Spade Type				Pow	ver Generation:	480V/60 Hz/3-Phase	
			САР	ACITIES A	ND DE	IVERY F	RATES		
Deadweight:		4,537 LT (4,610 MT)				Dec	ck Area:	196 ft x 50 ft (9,934 ft <sup>2</sup> )	
								59.9 m x 15.4 m (922.9 m²)	
<u>Deck Cargo:</u>		2,550 LT (2,	,				<u>ck Load Rating:</u>	1,200 lbs/ft <sup>2</sup> (6 MT/m <sup>2</sup> )	
<u> Dry Bulk:</u>		12,000 ft <sup>3</sup> (340 m <sup>3</sup> )					tem Pressure:	80 psi (5.5 bar)	
<u>iquid Mud:</u>					<u>Dis</u>	<u>charge Rate:</u>	1,100 GPM (250 m³/hr)		
Potable Water:		34,820 gal							
<u>Rig Fuel:</u>		335,461 gal (1,270 m <sup>3</sup> )					<u>charge Rate:</u>	1,400 GPM (318 m <sup>3</sup> /hr)	
Rig Water:		277,873 gal (1,052 m³)					<u>charge Rate:</u>	1,400 GPM (318 m <sup>3</sup> /hr)	
<b><u>Cooler Area:</u></b> 560 ft <sup>3</sup> (16 m <sup>3</sup> )					Fre	<u>ezer Area:</u>	525 ft <sup>3</sup> (15 m <sup>3</sup> )		

**ELECTRONICS** 

AIS, Auto Pilot, C-Nav, CCTV Cameras, Cyscan, Depth Sounder, DGPS w/ AIS, DSDL, EPIRB, GMDSS "A3", Gyro Compass, Joystick Control, Mag Compass, MAMS/VMS, Navtex, Public Phone System w/ loudhailer, Radascan, S-band Radar, SARTs, Speed Log, SSAS, VHF Radio, VHF Radio (Handheld), VSAT, Windbird, Xband Radar

## **ACCOMMODATIONS**

12 air conditioned/heated staterooms certified for 29 person berthing.

## **SPECIAL FEATURES**

Oil Spill Recovery:	ABS Capability Class 2	Recovered Oil Capacity:	12,996 bbl (2,066 m <sup>3</sup> ) (>60 °C FP)
Off-ship Firefighting:	FIFI I	Number of Fire Monitors:	2
		Total Flow Rate:	10,560 gal/min (2,400 m³/hr)
Deck Crane:	1 x North Pacific MCF-530	<u> Max Lift @ Max Radius:</u>	1.4 MT @ 30 ft
Roll Damping:	Passive, Anti-Roll Tank		

NOTICE: The information contained herein is provided solely for the convenience of reference, and Hornbeck does not warrant the accuracy or completeness of the data, which may vary from the current condition of the vessel or equipment. Hornbeck accepts no liability for the content of this document or for the consequences of any actions taken on the basis of the information provided, unless that information is subsequently confirmed in writing by an authorized representative.