



Service with Energy

HOS THUNDERFOOT

200 Offshore Supply Vessel



DIMENSIONS AND REGULATORY INFORMATION

Length:	190 ft 0 in (57.9 m)	Beam:	54 ft 0 in (16.5 m)	Draft Max:	13 ft 6 in (4.11 m)
Gross:	1,318 GT	Net:	395 NT	Draft Min:	8 ft 0 in (2.44 m)
IMO:	9211937	O.N.:	04013741323	Flag:	Mexico
Certifications:	Oceans-SOLAS				
Classifications:	Loadline, American Bureau of Shipping, +DPS-1, +A1, +AMS, OSR-C2				

PERFORMANCE

Max Speed:	13.0 kts	150 gal/hr (568 l/hr)
Cruise Speed:	10.0 kts	70 gal/hr (265 l/hr)

PROPULSION, MACHINERY AND STEERING

Main Engines:	2 x Caterpillar 3516B	Total Horsepower:	4,000 hp
Propellers:	FPP, High-Efficiency, 5-Blade	Propeller Diameter:	96in (2,438mm)
Primary Generators:	3 x Caterpillar 3406B	Total Rating:	750 kW
Bow Thruster:	1 x Brunvoll CPP Tunnel	Total Horsepower:	600 hp
Stern Thruster:	1 x SMI FPP Tunnel	Total Horsepower:	250 hp
Rudder:	Independent Steering, Schilling Fishtail	Power Generation:	480V/60 Hz/3-Phase

CAPACITIES AND DELIVERY RATES

Deadweight:	1,678 LT (1,705 MT)	Deck Area:	104ft x 46ft (4,784ft ²) 31.7m x 14.0m (444.4m ²)
Deck Cargo:	1,000 LT (1,016 MT)	Deck Load Rating:	1,024 lbs/ft ² (5 MT/m ²)
Dry Bulk:	7,000 ft ³ (198 m ³)	System Pressure:	80 psi (5.5 bar)
Potable Water:	54,562 gal (207 m ³)	Watermaker Cap.:	3,000 USG/day (11.4 m ³ /day)
Rig Fuel:	293,501 gal (1,111 m ³)	Discharge Rate:	550 GPM (125 m ³ /hr)
Rig Water:	148,567 gal (562 m ³)	Discharge Rate:	550 GPM (125 m ³ /hr)
Cooler Area:	400 ft ³ (11 m ³)	Freezer Area:	400 ft ³ (11 m ³)
Off-ship Firefighting Monitors:	1	Total Flow Rate:	1,250 gal/min (284 m ³ /hr)

ELECTRONICS

AIS, Auto Pilot, C-Nav, CCTV Cameras, Depth Sounder, DGPS, Fanbeam, GMDSS "A3", Gyro Compass, Joystick Control, Loudhailer, Mag Compass, MAMS/VMS, Nautronix JSDP 5000, Navtex, Public Phone System w/ loudhailer, SARTs, Single Side Band, VHF Radio, VHF Radio (Handheld), Windbird, X-band Radar

ACCOMMODATIONS

6 air conditioned/heated staterooms certified for 13 person berthing.
Additional deck berthing for 12 person(s)

SPECIAL FEATURES

Oil Spill Recovery:	ABS Capability Class 2	Recovered Oil Capacity:	3,590 bbl (571 m ³) (> 60 °C FP)
Crane:	2 x Hydra Pro 20 Ton Telescoping Boom	Max Lift @ Max Radius:	4.5 MT @ 37 ft
		Max Lift @ Min Radius:	18.1 MT @ 10 ft
Freezer/Chillers:	2 x 20ft Refrigerated ISO Containers	Personnel Transfer:	Swing Rope Station
Fenders:	2 x Yokohama Fenders per Side	Dry Stores:	2 x 20ft ISO Containers

NOTICE: The information contained herein is provided solely for the convenience of reference, and Hornbeck does not warrant the accuracy or completeness of the data, which may vary from the current condition of the vessel or equipment. Hornbeck accepts no liability for the content of this document or for the consequences of any actions taken on the basis of the information provided, unless that information is subsequently confirmed in writing by an authorized representative.