



Service with Energy

HOS WINDANCER

250EDF Offshore Supply Vessel



DIMENSIONS AND REGULATORY INFORMATION

Length:	250 ft 0 in (76.2 m)	Beam:	54 ft 0 in (16.5 m)	Draft Max:	14 ft 10 in (4.52 m)
Gross:	1,955 GT	Net :	586 NT	Draft Min:	8 ft 0 in (2.44 m)
IMO:	9472397	O.N.:	1205150	Flag:	U.S.
Certifications:	Oceans-SOLAS, SIP, USCG Subchapter I, USCG Subchapter L				
Classifications:	Loadline, American Bureau of Shipping, +DPS-2, +A1, +AMS, ACC				

PERFORMANCE

Max Speed:	14.0 kts	250 gal/hr (946 l/hr)
Cruise Speed:	10.0 kts	90 gal/hr (341 l/hr)

PROPULSION, MACHINERY AND STEERING

Main Engines:	2 x Caterpillar 3516	Total Horsepower:	6,000 bhp
Propellers:	CPP, High Efficiency, 4-Blade	Propeller Diameter:	106in (2,692mm)
Primary Generators:	3 x Caterpillar C 18	Total Rating:	1,020 kW
Bow Thruster:	2 x Brunvoll CPP Tunnel	Total Horsepower:	1,900 hp
Stern Thruster:	1 x Brunvoll CPP Tunnel	Total Horsepower:	950 hp
Rudder:	Independent Steering, Schilling Fishtail	Power Generation:	480/60/3

CAPACITIES AND DELIVERY RATES

Deadweight:	2,724 LT (2,768 MT)	Deck Area:	161ft x 45ft (7,245ft ²) 49.1m x 13.7m (673.1m ²)
Deck Cargo:	1,954 LT (1,985 MT)	Deck Load Rating:	1,024 lbs/ft ² (5 MT/m ²)
Dry Bulk:	7,800 ft ³ (221 m ³)	System Pressure:	80 psi (5.5 bar)
Brine:	8,240 bbl (1,310 m ³)	Discharge Rate:	407 GPM (93 m ³ /hr)
Liquid Mud:	8,240 bbl (1,310 m ³)	Discharge Rate:	407 GPM (93 m ³ /hr)
Potable Water:	30,850 gal (117 m ³)	Discharge Rate:	550 GPM (125 m ³ /hr)
Rig Fuel:	145,500 gal (551 m ³)	Discharge Rate:	550 GPM (125 m ³ /hr)
Rig Water:	302,850 gal (1,146 m ³)	Freezer Area:	400 ft ³ (11 m ³)
Cooler Area:	400 ft ³ (11 m ³)	Total Flow Rate:	3,000 gal/min (682 m ³ /hr)
Off-ship Firefighting Monitors:	1		

ELECTRONICS

AIS, Auto Pilot, C-Nav, CCTV Cameras, Cyscan, Depth Sounder, DGPS w/ AIS, DSDL, EPIRB, GMDSS "A3", Gyro Compass, Joystick Control, L-3 NMS 6000, Mag Compass, MAMS/VMS, Navtex, Public Phone System w/ loudhailer, SARTs, SSAS, VHF Radio, VHF Radio (Handheld), Windbird, X-band Radar

ACCOMMODATIONS

11 air conditioned/heated staterooms certified for 24 person berthing.

SPECIAL FEATURES

10 MT Deck Tugger, Bulk Compressor Air Dryer, Crane: 20t @ 10', Bulk Mud Ventilation Dust Filtering System, Electric Paddle Agitators (LM Tanks #6 & #8 P/S)

NOTICE: The information contained herein is provided solely for the convenience of reference, and Hornbeck does not warrant the accuracy or completeness of the data, which may vary from the current condition of t equipment. Hornbeck accepts no liability for the content of this document or for the consequences of any actions taken on the basis of the information provided, unless that information is subsequently confirmed in wri authorized representative.